



ELECTRONIC CONTROL

Simple and easy to use with an automatic mode: automatic management of ironing speed according to the selected temperature.
Digital display with speed and temperature.



EFFICIENCY

Good heat conduction thanks to the roll material and thickness: greater control of energy expenditure.
Automatic shutdown at 80°C (adjustable parameter).
Fumes circulation circuit from the bottom reducing energy consumption.
Radiant gas burners: +25% more productive



ROBUSTNESS

Roll driving by speed inverter: smooth operation preventing the wear of belts and mechanical elements.
Nomex quality feeding and ironing belts: high temperatures resistant.
Skinplate and stainless steel panels: long lasting.
Nickel plate cylinder: anti corrosive, more durable (not available in model 200mm).



ERGONOMICS

Acoustic comfort: <65 dB
Appropriate operating height: 990mm feeding belts.
Minimal encumbrance: space saving, suitable for most spaces.
Electronic control with Auto mode: easy to use, optimized ironing speed.



MAINTENANCE

Easy access to all components on both sides of the machine.
Basic connections: electrical connection and air extraction.



OTHERS

Dries and irons flat linen from a high spin washer extractor in a single operation.
Front feeding and return.
Built-in cool down system.
Polished steel roll Ø 325mm.
Roll lenght: 2.000mm, 2.600mm and 3.300mm.
Heating: electric, gas (atmospheric or radiant burner).
CE standard



OPTIONS

- EFFICIENT IRON: Humidity control Ø 325
- Nickel plated roll CM-2632
- Gas LPG option (Propan)
- Maritime wooden packing for CM-2632
- Gas NG option (Natural Gas)
- 230V 1~ + N 50Hz CM-2632 G ECO-ENERGY
- 230V 1~ + N 60Hz CM-2632 G ECO-ENERGY
- 230V 3~ 50/60Hz CM-2632 E ECO-ENERGY
- 440V 3~ 50/60Hz CM-2032 E ECO-ENERGY (marine)
- 440V 3~ 50/60Hz CM-2632 E ECO-ENERGY (marine)

GENERAL DETAILS		UNIT.	CM-2632 ECO-ENERGY M	
Theoretical production Electric heating*		Kg/h	60	
		lb/h	132	
Theoretical production Gas atmo heating*		Kg/h	N/A	
		lb/h	N/A	
Theoretical production Radiant gas heating*		Kg/h	75	
		lb/l	165	
Roll Ø		mm	325	
		inch	12,80	
Working width		mm	2.600	
		inch	102,4	
Height floor-feeding belts		mm	990	
		inch	39,0	
Working speed		m/min	1,5-12	
		ft/min	4.9-39	
Electronic control		-	Sí	
No. Programs		-	2	
Length folder		-	N/A	
Large surface contact with linen		-	270°	
POWER				
Electric mod.: heating power		Kw	40,5	
Electric mod: Total electric power		Kw	41,02	
Gas mod.: heating power		Kw	55	
Gas mod.: total electric power		Kw	0,77	
Steam mod.: heating power		Kg/h	-	
Roll motor power		Kw	0,41	
Fan motor power		Kw	0,18 x 2	
CONNECTIONS			E	G
Tension 230V - I + N + T		Nº x mm² / A	N/A	3 x 2,5 / 6A
		nº x AWG/A	N/A	3 x 13 / 6A
Tension 230V - III + T		Nº x mm² / A	4 x 25 / 125A	4 x 2,5 / 6A
		nº x AWG/A	4 x 3 / 100A	3 x 13 / 6A
Tension 400V - III + N + T		Nº x mm² / A	5 x 16 / 63A	5 x 2,5 / 6A
		nº x AWG/A	5 x 5 / 63A	5 x 13 / 6A
Ø Gas inlet		BSP	1/2"	
Ø Steam inlet		BSP	-	
Ø Condensed (Steam models)		BSP	-	
OVERALL DIMENSIONS / PACKING DIMENSIONS				
Net width / Gross width		mm	3.202 / 3.430	
		inch	126,1 / 135,0	
Net depth / gross depth		mm	686 / 770	
		inch	27 / 30,3	
Net height / gross height		mm	1.112 / 1.400	
		inch	43,8 / 55,1	
Net weight / gross weight		kg	545 / 585	
		lbs	1.202 / 1.290	
Net volume / Gross volume		m³	2,44 / 3,70	
		f³	86,26 / 130,58	
OTHERS				
No. Fume outlet		Nº	2	
Ø Fume outlet		mm	98	
		inch	3,86	
Air Flow		m³/h	1.000	
		cfm	589	
Sound level		dB	63	
Evaporation power		l/h	34	
		USgallon/h	8,9	
Additional ELECTRIC POWER with folder option		-	-	

Additional ELECTRIC POWER with folder+rear exit option	-	-
--	---	---

* 45% moisture

	A	B	C	D	E	F	G	H	I	J
CM-2032 ECO-ENERGY M	2.552	2.446	900	750	2.110	980	1.112	140	746	686
CM-2632 ECO-ENERGY M	3.202	3.096	900	750	2.760	980	1.112	140	746	686
CM-3332 ECO-ENERGY M	3.852	3.746	900	750	3.410	980	1.112	140	746	686