



### ELECTRONIC CONTROL

M programmer: push buttons to control temperature and time.



### OUTSTANDING FEATURES

Reversing drum action as standard.  
Galvanised steel drum.  
Frequency inverter as standard.



### EFFICIENCY

Big fluff filter.



### VERSATILITY

Make to order - customisation.  
OPL > Coin laundry - Standard OPL model easily trasformable to coin laundry.



### ERGONOMICS

Biggest door diameters.  
Opening sense of door adjustable on site.



### MAINTENANCE

Hinged control panel: easy and ergonomic access.  
Technical menu: statistics for technicians and maintenance with external console (with console option).  
Easy to access to components.



### OTHERS

White painted panels.  
COOL DOWN - anti-wrinkle at the end of the cycle.  
Heating options: electric or gas.  
CE approved



### OPTIONS

- Natural gas heated tumble dryer
- Opposite door opening
- Back panel with air filter
- M programmer display
- Maritime wooden packing DLM-22
- 400V 3N 60 Hz DLM-11-35
- 230V 3~ 50 Hz DLM-22/28/35 E
- 230V 3~ 60 Hz DLM-22/28/35 E
- 230V 3~ 60 Hz DLM-35 G/S
- 440/480V 3~ 60 Hz DLM-22/28/35
- Several payment systems for self-service

| CAPACITY & DRUM                       |              | UNIT.          | DLM-22        |
|---------------------------------------|--------------|----------------|---------------|
| Capacity 1/18                         |              | Kg             | 24,4          |
|                                       |              | lb             | 53,9          |
| Capacity 1/20                         |              | Kg             | 22,0          |
|                                       |              | lb             | 48,5          |
| Ø Drum                                |              | mm             | 835           |
|                                       |              | inch           | 32,87         |
| Drum length                           |              | mm             | 800           |
|                                       |              | inch           | 31,5          |
| Drum volume                           |              | l              | 440           |
|                                       |              | cu ft          | 15,54         |
| Ø Door hole                           |              | mm             | 574           |
|                                       |              | inch           | 22,60         |
| Door center height                    |              | mm             | 1.030         |
|                                       |              | inch           | 40,55         |
| Height from floor to bottom of door   |              | mm             | 672           |
|                                       |              | inch           | 26,46         |
| ELECTRIC HEATING                      |              |                |               |
| Evaporation capacity                  |              | L/h            | 17            |
|                                       |              | US gallon/h    | 4,5           |
| Hourly output                         |              | Kg/h           | 34            |
|                                       |              | lb/h           | 75            |
| Installed heating power               |              | kW             | 24            |
| Installed electrical power            |              | kW             | 24,97         |
| GAS HEATING                           |              |                |               |
| Evaporation capacity (gas model)      |              | L/h            | 20            |
|                                       |              | US gallon/h    | 5,283         |
| Hourly output (gas model)             |              | Kg/h           | 40            |
|                                       |              | lb/h           | 88,2          |
| Installed gas heating power           |              | kcal/h         | 26655         |
|                                       |              | Btu/h          | 105776        |
| Installed gas heating power           |              | kW             | 31            |
| Installed electrical power            |              | kW             | 0,97          |
| Instant propane gas consumption (G31) |              | Kg/h           | 2,66          |
|                                       |              | lb/h           | 5,86          |
| Instant natural gas consumption (G20) |              | m³/h           | 3,28          |
|                                       |              | cfm            | 1,93          |
| Ø Gas inlet                           |              | BSPP ISO 228-1 | 1/2"          |
| POWER AND VENTILATION                 |              |                |               |
| Drum motor power                      |              | kW             | 0,37          |
| Fan motor power                       |              | kW             | 0,55          |
| Nominal air flow rate                 |              | m³/h           | 1.200         |
|                                       |              | cfm            | 706           |
| Ø Fume exhaust                        |              | mm             | 200           |
|                                       |              | inch           | 7,87          |
| HEAT EMISSION                         |              |                |               |
| Maximum total heat emission           |              | kW             | 2,4           |
|                                       |              | Btu/h          | 8194          |
| Max. front heat emission              |              | kW             | 1,7           |
|                                       |              | Btu/h          | 5736          |
| CONNECTIONS                           |              | E              | G / S         |
| Tension 230V - I + N + T              | Nº x mm² / A | -              | 3 x 1,5 / 16A |
| Tension 230V - III + T                | Nº x mm² / A | 4 x 25 / 80A   | 3 x 1,5 / 16A |
| Tension 400V - III + N + T            | Nº x mm² / A | 5 x 10 / 40A   | 3 x 1,5 / 16A |
| NET DIMENSIONS / D. WITH PACKING      |              |                |               |
| Net / gross width                     | mm           | 890 / 970      |               |
|                                       | inch         | 35 / 38,2      |               |

|                    |      |               |
|--------------------|------|---------------|
| Net / gross depth  | mm   | 1.255 / 1.345 |
|                    | inch | 49,4 / 53     |
| Net / gross height | mm   | 1.812 / 1.940 |
|                    | inch | 71,3 / 76,4   |
| Net / gross weight | Kg   | 210 / 230     |
|                    | lb   | 463 / 507     |
| OTHERS             |      |               |
| Sound level        | dB   | 65            |

